

SUPPLEMENTARY CATALOG

2021

山东吉朗一家专业生产免挖基
坑升降台的厂家。

**GEE 吉朗
LONG**



山东吉朗机械设备有限公司
公司地址：山东省临沂市罗庄区化武路美鑫国际金属物流城 E-2
网址：www.geelonggroup.com
联系电话：

400-967-1778



山东吉朗机械设备有限公司
SHANDONG GEELONG MACHINERY EQUIPMENT CO., LTD
山东-临沂

1300*1300mm升降台 1300*1300mm table lifter



1300*1300mm 升降台

设备参数 machine specification

最大载重 Max.loading	3T
闭合高度 closed height	250mm
提升高度 lifting height	1000mm
电机功率 motor power	3kw
手动升降控制方式 (标配)Manual lifting control method	脚踏开关 Foot switch
泵站 hydraulic station	无锡液压站 WUXI brand hydraulic station
保护方式 Protection method	机械加电控行程保护 Mechanical and electric control stroke
电机品牌 motor brand	南京控特
外形尺寸(可定做) machine dimension	1300*1300*250mm (customized)



1300*1300mm 双层升降台

设备参数 machine specification

最大载重 Max.loading	3T
闭合高度 closed height	450mm
提升高度 lifting height	1800mm
电机功率 motor power	3kw
手动升降控制方式 (标配)Manual lifting control method	脚踏开关 Foot switch
泵站 hydraulic station	无锡液压站 WUXI brand hydraulic station
保护方式 Protection method	机械加电控行程保护 Mechanical and electric control stroke
电机品牌 motor brand	南京控特
外形尺寸(可定做) machine dimension	1300*1300*450mm (customized)

辊式输送平台 roller type conveyor table



专业生产定制各种尺寸辊式输送平台。根据客户设备需求进行设计布局。可以提高整厂自动化运行水平，完全可以代替叉车人工进行自动化输送板材。

Specializing in the production of customized roller conveyor platforms of various sizes. Design layout according to customer equipment requirements. It can improve the automatic operation level of the whole plant, and can completely replace the forklift to automatically transport the boards.



E90 免挖基坑升降台 E90 non-ground foundation table lifter



最高位90cm

最低位9cm

设备优势 machine advantage

- 1, 闭合后高度只有 9cm, 不需要挖基坑, 布局灵活, 移动方便。
The height after closing is only 9cm, no need to dig a foundation pit, flexible layout and easy to move.
- 2, 设备所有部件采用精密机床及激光切割加工而成, 精密度高。
All parts of the equipment are processed by precision machine tools and laser cutting, with high precision.
- 3, 液压站采用精密液压动力单元, 静音防尘免维护。
The hydraulic station adopts a precision hydraulic power unit, which is silent, dust-proof and maintenance-free.
- 4, 顶板烤漆, 色泽鲜艳, 表面光洁度好
The top plate is painted with bright color and good surface finish.
- 5, 自动升降采用激光传感器, 精度高, 量程大
Laser sensor is used for automatic lifting, with high precision.
- 6, 所有滚轮, 滚轴嵌有铜制耐磨套, 耐用寿命长。
All rollers inside are embedded with copper wear-resistant sleeves, which have a long durability.

设备参数 machine specification

最大载重 Max.loading	1.5T
闭合高度 closed height	90mm
提升高度 lifting height	900mm
顶板颜色 Top plate color	红色, 黄色, 其他颜色可定制 Red / yellow / optional
电机功率 motor power	1.5kw
手动升降控制方式 (标配)	脚踏开关
Manual lifting control method	Foot switch
自动升降控制方式 (可选)	激光传感器
Automatic lifting control method	laser sensor
泵站 hydraulic station	液压动力单元
保护方式 Protection method	机械加电控行程保护
	Mechanical and electric control stroke
外形尺寸 machine dimension	1350*1500*90mm

E150 免挖基坑升降台 E150 non-ground foundation table lifter



最高位 1m

最低位 15cm

设备优势 machine advantage

- 1, 闭合后高度只有 15cm, 不需要挖基坑, 布局灵活, 移动方便。
The height after closing is only 15cm, no need to dig a foundation pit, flexible layout and easy to move.
- 2, 设备所有部件采用精密机床及激光切割加工而成, 精密度高。
All parts of the equipment are processed by precision machine tools and laser cutting, with high precision.
- 3, 采用精密高档无锡液压站, 耐用质量好, 立式电控柜, 操作方便。
Precision WUXI brand hydraulic station, which is durable and good quality.
- 4, 顶板烤漆, 色泽鲜艳, 表面光洁度好
Vertical electric control cabinet, easy to operate.
- 4, 顶板烤漆, 色泽鲜艳, 表面光洁度好
The top plate is painted with bright color and good surface finish.
- 5, 自动升降采用激光传感器, 精度高, 量程大
Laser sensor is used for automatic lifting, with high precision.
- 6, 所有滚轮, 滚轴嵌有铜制耐磨套, 耐用寿命长。
All rollers inside are embedded with copper wear-resistant sleeves, which have a long durability.

设备参数 machine specification

最大载重 Max.loading	3T / 4T / 5T
闭合高度 closed height	150mm
提升高度 lifting height	1000mm
顶板颜色 Top plate color	红色, 黄色, 其他颜色可定制 Red / yellow / optional
电机功率 motor power	3kw / 4KW
手动升降控制方式 (标配)	脚踏开关
Manual lifting control method	Foot switch
自动升降控制方式 (可选)	激光传感器
Automatic lifting control method	laser sensor
泵站 hydraulic station	无锡液压站 WUXI brand hydraulic station
保护方式 Protection method	机械加电控行程保护
	Mechanical and electric control stroke
外形尺寸 machine dimension(可定做)	1400*2000*150mm(customized)



免挖基坑站人升降台 non-ground foundation table lifter



最高位1800mm



最低位250mm

设备参数 machine specification

最大载重 Max.loading	3T / 4T / 5T
闭合高度 closed height	250mm
提升高度 lifting height	1800mm
电机功率 motor power	3kw / 4KW
手动升降控制方式 (标配) Manual lifting control method	脚踏开关 Foot switch
核载操作人员 Nuclear operator	2 人 two persons
泵站 hydraulic station	无锡液压站 WUXI brand hydraulic station
保护方式 Protection method	机械加电控行程保护 Mechanical and electric control stroke
外形尺寸 machine dimension(可定做)	1200*2400*250mm(customized)

辊式升降台 table lifter with rollers

专业生产定制各种尺寸辊式升降台，应用于板材行业，家具行业等

Specializing in the production and customization of various sizes of roller lifting tables, which are used in the board industry, furniture industry, etc.



1200*2400mm
动力辊式升降台



1200*2400mm
无动力辊式升降台

600mm*2000mm
无动力辊式升降台





250免挖基坑升降台 250 non-ground foundation table lifter



设备优势 machine advantage

- 1, 闭合后高度只有 25cm, 不需要挖基坑, 布局灵活, 移动方便。
The height after closing is only 25cm, no need to dig a foundation pit, flexible layout and easy to move.
- 2, 设备采用国标钢板焊接而成, 经久耐用。
The equipment is welded with national standard steel plate, which is durable.
- 3, 采用精密高档无锡液压站, 耐用质量好。
Precision WUXI brand hydraulic station, which is durable and good quality.
- 5, 自动升降采用激光传感器, 精度高, 量程大
Laser sensor is used for automatic lifting, with high precision.

设备参数 machine specification

最大载重 Max.loading	3T / 4T / 5T
闭合高度 closed height	250mm
提升高度 lifting height	1800mm
电机功率 motor power	3kw / 4KW
手动升降控制方式 (标配) Manual lifting control method	脚踏开关 Foot switch
自动升降控制方式 (可选) Automatic lifting control method	激光传感器 laser sensor
泵站 hydraulic station	无锡液压站 WUXI brand hydraulic station
保护方式 Protection method	机械加电控行程保护 Mechanical and electric control stroke
外形尺寸 machine dimension(可定做)	1200*2400*250mm(customized)

叉车位升降台 forklift position table lifter



设备优势 machine advantage

- 1, 叉车凹槽设计, 方便装卸货物。
The forklift groove design is convenient for loading and unloading goods.
- 2, 设备采用国标钢板焊接而成, 经久耐用。
The equipment is welded with national standard steel plate, which is durable.
- 3, 采用精密高档无锡液压站, 耐用质量好。
Precision WUXI brand hydraulic station, which is durable and good quality.
- 5, 自动升降采用激光传感器, 精度高, 量程大
Laser sensor is used for automatic lifting, with high precision.

设备参数 machine specification

最大载重 Max.loading	3T / 4T / 5T
闭合高度 closed height	350mm
提升高度 lifting height	1800mm
电机功率 motor power	3kw / 4KW
手动升降控制方式 (标配) Manual lifting control method	脚踏开关 Foot switch
自动升降控制方式 (可选) Automatic lifting control method	激光传感器 laser sensor
泵站 hydraulic station	无锡液压站 WUXI brand hydraulic station
保护方式 Protection method	机械加电控行程保护 Mechanical and electric control stroke
外形尺寸 machine dimension(可定做)	1200*2400*350mm(customized)